NSN 5935-00-368-9744

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-9744

View Offline at https://derobasegroup.com/nsi//0905-00-000-97-44
Body Style:
Straight type
Overall Length:
2.406 inches
Overall Height:
0.850 inches
Overall Width:
0.531 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Distance Between Mounting Facility Centers:
2.134 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
2000.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14 ty sdg military specification single material response single mating end

Included Contact Quantity:

17 single mating end single contact grouping

NSN 5935-00-368-9744

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mati
Precious Material And L

ing end single contact grouping

Location:

Contact surfaces gold

Precious Material And Weight:

0.017 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.