## NSN 5935-00-368-9746

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-9746

| Body Style:   |
|---|
| Straight type   |
| Overall Length:   |
| 2.406 inches  |
| Overall Height:   |
| 0.850 inches  |
| Overall Width:  |
| 0.531 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.128 inches  |
| Distance Between Mounting Facility Centers:   |
| 2.134 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 1 row of contacts inserted board single mating end  |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 10.0 single mating end single contact grouping  |
| Contact Maximum Ac Voltage Rating In Volts:   |
| 2000.0 single mating end single contact grouping  |
| Polarization Method:  |
| Contact to contact polarizing keys  |
| Connector Locking Method:   |
| Friction  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |
| Contact Material Specification:   |
| Qq-b-750, c0mp a federal specification single material response single mating end single contact grouping |
| Insert Material Specification:  |
| Mil-m-14 ty sdg military specification single material response single mating end                         |

Included Contact Quantity:

17 single mating end single contact grouping

## NSN 5935-00-368-9746

Electrical Receptacle Connector - Page 2 of 2



| II | ncı | lu | ae | ea | C | oni | a | CT | 1 ) | уp | е |  |
|----|-----|----|----|----|---|-----|---|----|-----|----|---|--|
|    |     |    |    |    |   | _ · | 1 |    |     |    |   |  |

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.017 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.