Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-369-1062

Body Style:

Right angle type

Overall Length:

Between 3.330 inches and 3.370 inches

Overall Height:

0.550 inches

Overall Width:

0.250 inches

Body Height:

0.400 inches

Environmental Protection:

Heat resistant and vibration resistant and corrosion resistant

Distance Between Mounting Facility Centers:

3.150 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-s-763 federal specification single material response single mating end single contact grouping



Guide Design And Location: D shape socket left-hand at 12 oclock **Insert Material Specification:** Mil-p-19833, ty gdi 30f military specification single material response single mating end **Included Contact Quantity:** 60 single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.060 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.