

View Online at <https://aerobasegroup.com/nsn/5935-00-370-2318>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top or bottom mount w/molded saddle and bushing

Overall Length:

Between 1.700 inches and 1.720 inches

Overall Height:

0.970 inches

Overall Width:

Between 0.990 inches and 1.010 inches

Mounting Hole Diameter:

Between 0.142 inches and 0.152 inches

Body Mounting Hole Accommodation Length:

Between 0.900 inches and 0.940 inches

Body Mounting Hole Accommodation Width:

Between 0.910 inches and 0.930 inches

Mounting Hole Style:

Rectangular, w/three mounting holes/slots

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

14

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.401 inches and 1.411 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.620 inches and 0.630 inches

Missing Contact Designation:

6th contact position and 10th contact position

Polarization Type:

Contact position

Projection Length Above Mounting Surface:

Between 0.215 inches and 0.225 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Contact Position Arrangement Style:

Quadruple in line

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Furnished Items And Quantity:

3 spacer and 3 nut and 3 stud

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300