NSN 5935-00-370-2420

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-370-2420

| inread Class: |
|--|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.720 inches |
| Overall Height: |
| 0.840 inches |
| Overall Width: |
| 1.230 inches |
| Environmental Protection: |
| Corrosion resistant and shock resistant and salt water resistant |
| Distance Between Mounting Facility Centers: |
| 2.281 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 75 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 750.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 1050.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Solid |
| Cond |
| Connector Locking Method: |
| |
| Connector Locking Method: |
| Connector Locking Method: Jackscrew-socket |

Contact Material:

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

NSN 5935-00-370-2420

Electrical Receptacle Connector - Page 2 of 2



| Contact Surface Treatment: |
|---|
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Chromate and gold |
| Shell Surface Treatment Specification: |
| Mil-c-5541, type 1, grade c, class 3 military specification single treatment response |
| Insert Material Specification: |
| Mil-m-14, type mdg military specification single material response single mating end |
| Included Contact Quantity: |
| 75 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact and body surfaces gold |
| Precious Material And Weight: |
| 0.175 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc and unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-14 spec. |