

View Online at <https://aerobasegroup.com/nsn/5935-00-372-1325>

**Body Style:**

Straight shape, external coupling w/strain relief

**Overall Length:**

Between 1.380 inches and 1.420 inches

**Overall Diameter:**

Between 0.480 inches and 0.520 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Cable Entrance Diameter:**

Between 0.240 inches and 0.280 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Snap ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Astm standard b-301, comp ht assn standard single material response single mating end single contact grouping

**Shell Material:**

Aluminum alloy 2024

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, class 1 military specification single treatment response

**Shell Material Specification:**

Qq-a-225/6, t4 federal specification single material response

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.007 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.