NSN 5935-00-378-0238

Thread Class:

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-378-0238



2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.328 inches **Overall Diameter:** Between 2.296 inches and 2.328 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 334.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.219 inches Thready Qty Per Inch (tpi): **Thread Size:** 1.750 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings

NSN 5935-00-378-0238

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Passivate
Included Contact Quantity:
4 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.046 gold grains, troy and 0.046 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
96906-ms27468 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0