## NSN 5935-00-378-1005

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-378-1005

**Thread Class:** 

2a and 2b and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.235 inches and 1.265 inches

**Overall Height:** 

0.557 inches

**Overall Width:** 

Between 0.250 inches and 0.280 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Distance Between Mounting Facility Centers:** 

Between 0.995 inches and 1.005 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

26 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

350.0 single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thread Length:

0.167 inches

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-378-1005

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.026 gold grains, troy and 0.026 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.