

View Online at <https://aerobasegroup.com/nsn/5935-00-378-1378>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape w/screw locks

Overall Length:

0.880 inches

Overall Height:

0.840 inches

Overall Width:

0.230 inches

Environmental Protection:

Salt water resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

7 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Size:

0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdc-f military specification single material response single mating end

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.007 gold grains, troy and 0.007 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.