Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-378-3595

Body Style:         Wall type         Overall Height:         1.718 inches         Overall Width:         1.703 inches         Body Length:         2.687 inches         Environmental Protection:         Heat resistant and cold resistant and humidity resistant         Distance Between Mounting Facility Centers:         3.281 inches         Mating End Quantity:         1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings         Contact Maximum Ac Voltage Rating In Volts:         208.0 single mating end all contact groupings
Overall Height:         1.718 inches         Overall Width:         1.703 inches         Body Length:         2.687 inches         Environmental Protection:         Heat resistant and cold resistant and humidity resistant         Distance Between Mounting Facility Centers:         3.281 inches         Mating End Quantity:         1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings
<ul> <li>1.718 inches</li> <li>Overall Width:</li> <li>1.703 inches</li> <li>Body Length:</li> <li>2.687 inches</li> <li>Environmental Protection:</li> <li>Heat resistant and cold resistant and humidity resistant</li> <li>Distance Between Mounting Facility Centers:</li> <li>3.281 inches</li> <li>Mating End Quantity:</li> <li>1</li> <li>Contact Position Arrangement Style:</li> <li>Nonstd single mating end</li> <li>Contact Removability:</li> <li>Nonremovable single mating end all contact groupings</li> <li>Contact Maximum Current Rating In Amps:</li> <li>30.0 single mating end all contact groupings</li> </ul>
Overall Width:         1.703 inches         Body Length:         2.687 inches         Environmental Protection:         Heat resistant and cold resistant and humidity resistant         Distance Between Mounting Facility Centers:         3.281 inches         Mating End Quantity:         1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings
<ul> <li>1.703 inches</li> <li>Body Length:</li> <li>2.687 inches</li> <li>Environmental Protection:</li> <li>Heat resistant and cold resistant and humidity resistant</li> <li>Distance Between Mounting Facility Centers:</li> <li>3.281 inches</li> <li>Mating End Quantity: <ol> <li>Contact Position Arrangement Style:</li> <li>Nonstd single mating end</li> <li>Contact Removability:</li> <li>Nonremovable single mating end all contact groupings</li> <li>Contact Maximum Current Rating In Amps:</li> <li>30.0 single mating end all contact groupings</li> </ol> </li> </ul>
Body Length:         2.687 inches         Environmental Protection:         Heat resistant and cold resistant and humidity resistant         Distance Between Mounting Facility Centers:         3.281 inches         Mating End Quantity:         1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings         Contact Maximum Ac Voltage Rating In Volts:
2.687 inches Environmental Protection: Heat resistant and cold resistant and humidity resistant Distance Between Mounting Facility Centers: 3.281 inches Mating End Quantity: 1 Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Environmental Protection: Heat resistant and cold resistant and humidity resistant Distance Between Mounting Facility Centers: 3.281 inches Mating End Quantity: 1 Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Heat resistant and cold resistant and humidity resistant Distance Between Mounting Facility Centers: 3.281 inches Mating End Quantity: 1 Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Distance Between Mounting Facility Centers: 3.281 inches Mating End Quantity: 1 Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings
3.281 inches Mating End Quantity: 1 Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Mating End Quantity:         1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings         Contact Maximum Ac Voltage Rating In Volts:
1         Contact Position Arrangement Style:         Nonstd single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         30.0 single mating end all contact groupings         Contact Maximum Ac Voltage Rating In Volts:
Contact Position Arrangement Style: Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Nonstd single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Nonremovable single mating end all contact groupings <b>Contact Maximum Current Rating In Amps:</b> 30.0 single mating end all contact groupings <b>Contact Maximum Ac Voltage Rating In Volts:</b>
Contact Maximum Current Rating In Amps: 30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
30.0 single mating end all contact groupings Contact Maximum Ac Voltage Rating In Volts:
Contact Maximum Ac Voltage Rating In Volts:
208.0 single mating end all contact aroupings
Polarization Method:
Contact
Connector Locking Method:
Friction
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Screw single mating end all contact groupings
Contact Material Specification:
Qq-b-613 federal specification single material response single mating end all contact groupings
Insert Material Specification:
Mil-n-18352 military specification single material response single mating end
Included Contact Quantity:
3 single mating end 2nd contact grouping
Included Contact Type:
Curved pin w/inside lip single mating end 1st contact grouping

## NSN 5935-00-378-3595

Electrical Receptacle Connector - Page 2 of 2



Color:

Yellow

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-n-18352 spec.