## NSN 5935-00-386-7149

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-386-7149 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.375 inches **Overall Height:** 0.937 inches **Overall Width:** 0.937 inches **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Distance From Mounting Shoulder To Front Face:** 0.718 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** "10-5, 10-05" single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 0.562 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-00-386-7149

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Rhodium single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Stainless steel **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces rhodium and contact surfaces silver **Precious Material And Weight:** 0.005 rhodium grains, troy and 0.005 silver grains, troy **Precious Material:** Rhodium and silver **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure: Demilitarization:** No