# NSN 5935-00-386-7176

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-386-7176

## Thread Class:

2a and 2a

## Thread Direction:

Right-hand and right-hand

## Body Style:

Straight shape, external coupling

### **Overall Length:**

Between 1.390 inches and 1.422 inches

### **Overall Diameter:**

Between 0.745 inches and 0.755 inches

## **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

## Distance From Mounting Shoulder To Front Face:

Between 0.165 inches and 0.176 inches

## **Mounting Facility Thickness:**

Between 0.120 inches and 0.130 inches

## Threaded Device Type:

Coupling facility and mounting bushing

## Mating End Quantity:

2

## **Contact Position Arrangement Style:**

Nonstd all mating ends

## **Contact Removability:**

Nonremovable all mating ends single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

## **Contact Maximum Frequency Rating:**

10000.0 megahertz all mating ends single contact grouping

## Shell Type:

Solid

### **Connector Locking Method:**

Externally threaded shell

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

## Thready Qty Per Inch (tpi):

28 and 28

### Thread Size:

0.500 inches and 0.063 inches

### **Contact Material:**

Copper alloy all mating ends single contact grouping

## **Contact Surface Treatment:**

Gold all mating ends single contact grouping

## NSN 5935-00-386-7176

Connector Adapter - Page 2 of 2



### Insert Material:

Plastic polytetrafluoroethylene all mating ends

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response all mating ends single contact grouping

### **Contact Material Specification:**

Qq-c-530, 1/2 @h military specification single material response all mating ends single contact grouping

### Shell Material:

Copper alloy

### **Shell Surface Treatment:**

Silver

### Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

### **Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

### **Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends

### **Included Contact Quantity:**

1 2nd mating end single contact grouping

### **Bushing Accommodation Hole Shape:**

Round w/flat

### Included Contact Type:

Coaxial socket all mating ends single contact grouping

### **Special Features:**

Contac designation tnc

### **Precious Material And Location:**

Contact surfaces gold and body surface silver

### **Precious Material And Weight:**

0.010 gold grains, troy and 0.100 silver grains, troy

### **Precious Material:**

Gold and silver

## **Thread Series Designator:**

Unef and unef

Shelf Life:

N/a

### Unit Of Measure:

---

```
Demilitarization:
```

No

Fiig:

A039b0

### Mil-std (military Standard):

spec.