

View Online at <https://aerobasegroup.com/nsn/5935-00-387-0931>

**Body Style:**

Straight shape threaded

**Overall Length:**

Between 0.635 inches and 0.647 inches

**Overall Diameter:**

Between 1.076 inches and 1.088 inches

**Environmental Protection:**

Humidity resistant

**Distance From Mounting Shoulder To Front Face:**

0.534 inches

**Mounting Facility Thickness:**

0.109 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-62 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Rhodium single mating end all contact groupings and silver single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

19 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Special Features:**

Solder flange mtd

**Precious Material And Location:**

Contact surfaces rhodium and contact surfaces silver

**Precious Material And Weight:**

0.020 rhodium grains, troy and 0.020 silver grains, troy

**Precious Material:**

Rhodium and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0