

View Online at <https://aerobasegroup.com/nsn/5935-00-387-2979>

Body Style:

Straight shape, w/ or w/o cover

Mating End Quantity:

2

Contact Position Arrangement Style:

"3, 5-15" single mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Terminal Location:

Side all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Screw all mating ends all contact groupings

Shell Material:

Aluminum

Insert Material Specification:

Mil-m-14, type cfg military specification single material response single mating end

Included Contact Quantity:

2 2nd mating end 2nd contact grouping

Included Contact Type:

U-socket 2nd mating end 1st contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.