

View Online at <https://aerobasegroup.com/nsn/5935-00-387-2979>

**Body Style:**

Straight shape, w/ or w/o cover

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

"3, 5-15" single mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 all mating ends all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Terminal Location:**

Side all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Screw all mating ends all contact groupings

**Shell Material:**

Aluminum

**Insert Material Specification:**

Mil-m-14, type cfg military specification single material response single mating end

**Included Contact Quantity:**

2 2nd mating end 2nd contact grouping

**Included Contact Type:**

U-socket 2nd mating end 1st contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.