NSN 5935-00-390-8288

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-390-8288 **Thread Class:** 2b and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape **Overall Length:** 1.485 inches **Overall Height:** 4.150 inches **Overall Width:** 0.305 inches **Distance Between Mounting Facility Centers:** Between 1.260 inches and 1.270 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thread Length: 0.226 inches **Thread Size:** 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment: Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

NSN 5935-00-390-8288

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
18.000 in. Wire lead
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0