Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-390-8288

# Thread Class:

2b and 2a

# **Thread Direction:**

Right-hand and right-hand

# **Body Style:**

Straight shape

# **Overall Length:**

1.485 inches

#### **Overall Height:**

4.150 inches

**Overall Width:** 

0.305 inches

## **Distance Between Mounting Facility Centers:**

Between 1.260 inches and 1.270 inches

#### Threaded Device Type:

Coupling facility and mounting stud

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

37 single mating end

# Contact Removability:

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Polarization Method:**

Mating end

## Shell Type:

Solid

## **Connector Locking Method:**

Jackscrew-socket

#### Thread Length:

0.226 inches

#### **Thread Size:**

0.086 inches and 0.086 inches

## **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic single mating end



# **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 37 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** 18.000 in. Wire lead **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.037 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A039b0

---