## NSN 5935-00-391-5761

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-391-5761

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 1.078 inches and 1.140 inches

**Overall Height:** 

1.781 inches

**Overall Width:** 

1.781 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.432 inches and 1.442 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.432 inches and 1.442 inches

**Distance From Mounting Shoulder To Front Face:** 

0.531 inches

**Mating End Quantity:** 

VIC

**Contact Position Arrangement Style:** 

61-21 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1000.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Spring friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-00-391-5761

**Insert Material:** 

Electrical Receptacle Connector - Page 2 of 2



Rubber synthetic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.