

View Online at <https://aerobasegroup.com/nsn/5935-00-397-2223>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

0.953 inches

Overall Height:

0.672 inches

Overall Width:

0.250 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

1.5 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Length:

0.125 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Contact Material:

Copper alloy 360 all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic fluorocarbon all mating ends

Contact Surface Treatment Specification:

Mil-g-45204b, type 1, grade c military specification all treatment responses all mating ends all contact groupings

Contact Material Specification:

Qq-b-626 federal specification all material responses all mating ends all contact groupings

Shell Material:

Copper alloy 360

Shell Surface Treatment:

Gold

Shell Material Specification:

Qq-b-626, 1/2 h federal specification single material response

Insert Material Specification:

L-p-403 federal specification all material responses all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204b spec.