NSN 5935-00-399-3106

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-399-3106 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 3.047 inches and 3.079 inches **Overall Height:** Between 1.995 inches and 2.005 inches **Overall Width:** Between 1.995 inches and 2.005 inches **Unthreaded Mounting Hole Diameter:** Between 0.252 inches and 0.262 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.432 inches and 1.442 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches **Distance From Mounting Shoulder To Front Face:** Between 0.859 inches and 0.891 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 10000.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

18

Thread Size:

1.250 inches

NSN 5935-00-399-3106

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Lc-hv polarized
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0