NSN 5935-00-400-4758

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-400-4758 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.875 inches **Overall Diameter:** 0.969 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

NSN 5935-00-400-4758Electrical Plug Connector - Page 2 of 2



| Terminal Type: |
|--|
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 3 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.003 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |