Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-400-8089

#### **Body Style:**

Straight edge type w/mounting flange

## **Overall Length:**

Between 6.464 inches and 6.474 inches

## **Overall Height:**

Between 0.401 inches and 0.411 inches

#### **Overall Width:**

Between 0.433 inches and 0.443 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.122 inches and 0.128 inches

## Distance Between Mounting Facility Centers:

Between 6.212 inches and 6.226 inches

#### **Board Accommodated Length:**

5.901 inches single board and 5.911 inches single board

## **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

## Mating End Quantity:

1

# Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Wire wrap single mating end single contact grouping

# Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

#### Included Contact Quantity:

72 single mating end single contact grouping

#### **Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-m-19833 spec.