NSN 5935-00-401-7368

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-401-7368 **Thread Class:** 2b **Thread Direction:** Right-hand **Overall Length:** 1.187 inches **Overall Height:** 1.040 inches **Overall Width:** 1.187 inches **Environmental Protection:** Moisture proof Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.906 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Latch **Thread Size:** 0.112 inches **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Ceramic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping

Iron

Shell Material:

NSN 5935-00-401-7368

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 61 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.061 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.