

View Online at <https://aerobasegroup.com/nsn/5935-00-401-7411>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.266 inches

Overall Height:

1.562 inches

Overall Width:

1.562 inches

Environmental Protection:

Fuel resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

0.905 inches

Threaded Device Type:

Back shell and mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

20-39 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

850.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18 and 40

Thread Size:

1.312 inches and 0.112 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Included Contact Quantity:

37 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.039 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0