## NSN 5935-00-402-1043

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-402-1043

**Thread Class:** 2a and 2a and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.309 inches **Overall Diameter:** 0.500 inches **Environmental Protection:** Heat resistant **Distance From Mounting Shoulder To Front Face:** 0.379 inches **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 32 and 32 and 32 **Thread Size:** 0.250 inches and 0.312 inches and 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Plastic fluorocarbon single mating end **Terminal Type:** 

Solder well single mating end single contact grouping

Silver

**Shell Surface Treatment:** 

## NSN 5935-00-402-1043

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Terminal gold and shell silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
31876-cr3kb4-35 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unef and unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No