## NSN 5935-00-402-7009

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-402-7009

**Body Style:** 

Straight shape, thru-hole mount, external coupling

**Overall Length:** 

1.453 inches

**Overall Diameter:** 

0.938 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:** 

Between 0.400 inches and 0.431 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

8-4 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

0.0

Shell Type:

Potting

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Potting type

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 grade e federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416 type 2, cl 3 federal specification single treatment response

## NSN 5935-00-402-7009

Electrical Receptacle Connector - Page 2 of 2



## **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Solder flange mount **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.