NSN 5935-00-402-7016

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-402-7016

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.328 inches

Overall Diameter:

1.142 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

330.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

NSN 5935-00-402-7016

Electrical Plug Connector - Page 2 of 2



Precious Material And Weight:

 $0.019 \ \text{gold} \ \text{grains}, \ \text{troy} \ \text{and} \ 0.019 \ \text{silver} \ \text{grains}, \ \text{troy}$

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0