NSN 5935-00-402-9019

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-402-9019

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
0.930 inches
Overall Height:
2.000 inches
Overall Width:
3.875 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
3.500 inches
Distance From Mounting Shoulder To Front Face:
0.656 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
25-104 single mating end
Polarization Method:
Jackscrew and shell
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 32
Thread Size:
0.164 inches and 0.164 inches and 0.138 inches
Insert Material:
Plastic diallyl phthalate single mating end

Shell Material: Aluminum alloy

NSN 5935-00-402-9019

Mil-m-14 spec.

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Shell Guide Type And Location Designator:
A slot
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):