

View Online at <https://aerobasegroup.com/nsn/5935-00-402-9100>

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.531 inches

Overall Height:

1.578 inches

Overall Width:

1.578 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.245 inches and 1.255 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.566 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

142.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0