## NSN 5935-00-402-9102

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-402-9102

**Body Style:** 

Straight shape, external coupling w/backshell

**Overall Length:** 

1.531 inches

**Overall Height:** 

1.578 inches

**Overall Width:** 

1.578 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.245 inches and 1.255 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.556 inches and 0.566 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

22-55 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

200.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

314.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

NSN 5935-00-402-9102 Electrical Receptacle Connector - Page 2 of 2



| Insert Material:                                    |
|---|
| Plastic tetrafluoroethylene single mating end       |
| Terminal Type:                                      |
| Crimp single mating end single contact grouping     |
| Shell Material:                                     |
| Aluminum alloy                                      |
| Shell Surface Treatment:                            |
| Cadmium   |
| Included Contact Quantity:                          |
| 55 single mating end single contact grouping        |
| Included Contact Type:                              |
| Round pin single mating end single contact grouping |
| Precious Material And Location:                     |
| Contact surfaces gold                               |
| Precious Material And Weight:                       |
| 0.055 gold grains, troy                             |
| Precious Material:                                  |
| Gold  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| No  |
| Fiig:   |
| A039b0  |
|   |