## NSN 5935-00-403-2122

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-403-2122 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.703 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.388 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 1800.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.255 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Copper alloy terminal

Material:

Plastic insulator

## **NSN 5935-00-403-2122** Tip Jack - Page 2 of 2



| Precious Material And Location:  |
|--|
| Spring surface gold  |
| Precious Material:   |
| Gold   |
| Surface Treatment:   |
| Gold and copper spring   |
| Surface Treatment:   |
| Gold spring and copper spring  |
| Test Data Document:  |
| 31349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Jnef   |
| Specification Data:  |
| 31349-mil-c-39024 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Filg:  |
| 403400   |
|  |
|  |