## NSN 5935-00-403-2122

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-403-2122 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.703 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.388 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 1800.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.255 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Copper alloy terminal

Material:

Plastic insulator

## **NSN 5935-00-403-2122** Tip Jack - Page 2 of 2



Precious Material And Location:
Spring surface gold
Precious Material:
Gold
Surface Treatment:
Gold and copper spring
Surface Treatment:
Gold spring and copper spring
Test Data Document:
31349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jnef
Specification Data:
31349-mil-c-39024 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
403400