Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-404-2333

Body Style:

Straight shape, external coupling

Overall Length:

1.166 inches

Overall Height:

1.562 inches

Overall Width:

1.562 inches

Environmental Protection:

Moisture resistant and vibration proof and corrosion resistant and solvent resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

0.556 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Glass single mating end and resin synthetic single mating end

Terminal Type:

Solder well single mating end all contact groupings



Shell Material: Aluminum **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 47 single mating end 3rd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.087 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0