## NSN 5935-00-404-6739

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-404-6739 **Thread Class:** 2a and 2a and 2b **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape, flush mount **Overall Height:** 2.156 inches **Overall Width:** 2.290 inches **Environmental Protection:** Pressure proof and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.440 inches **Threaded Device Type:** Coupling facility and back shell **Mating End Quantity:** 15 **Contact Position Arrangement Style:** 80 single mating end **Polarization Method:** Polarization boss and guide pin/socket Shell Type: Solid **Connector Locking Method:** Jackscrew-socket and friction **Thread Size:** 0.250 inches and 0.250 inches **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic epoxy single mating end or plastic phenolic single mating end **Shell Material:** Steel and copper alloy **Insert Material Specification:** Mil-p-19833, type gdi-30f military specification single material response single mating end **Thread Series Designator:** Unf and unef Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5935-00-404-6739

Electrical Receptacle Connector Body - Page 2 of 2



Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.