## NSN 5935-00-404-8730

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-404-8730

**Body Style:** Straight shape **Overall Length:** Between 2.874 inches and 2.890 inches **Overall Height:** 0.914 inches **Overall Width:** Between 0.730 inches and 0.746 inches **Unthreaded Mounting Hole Diameter:** Between 0.119 inches and 0.129 inches **Distance Between Mounting Facility Centers:** Between 2.557 inches and 2.567 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Insert Material Specification:**

Mil-m-19833, ty gdi-30f military specification single material response single mating end

## NSN 5935-00-404-8730

Electrical Receptacle Connector - Page 2 of 2



ncluded	Contact	Quantity:
---------	---------	-----------

50 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold and contact surface silver

**Precious Material And Weight:** 

0.050 gold grains, troy and 0.050 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.