Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-404-8874

Thread Class:
2b
Thread Direction:
Right-hand
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.281 inches
Overall Width:
3.562 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
"3, 10-30" single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
30.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end all contact groupings
Polarization Method:
Contact
Thread Size:
0.138 inches
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Tin single mating end all contact groupings
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Screw single mating end all contact groupings
Insert Material Specification:
Mil-m-14, type cfg military specification single material response single mating end
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
L-socket single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.