

View Online at <https://aerobasegroup.com/nsn/5935-00-404-8914>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Overall Length:

2.203 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Qty Per Inch (tpi):

18 and 24

Thread Size:

1.250 inches and 0.625 inches

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

2 single mating end single contact grouping

Precious Material And Location:

Contact surfaces and shell surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0