Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-404-8979

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.438 inches
Overall Height:
Between 2.219 inches and 2.281 inches
Overall Width:
Between 2.219 inches and 2.281 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.168 inches and 0.183 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.745 inches and 1.755 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.745 inches and 1.755 inches
Distance From Mounting Shoulder To Front Face:
Between 0.875 inches and 0.906 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.438 inches and 0.625 inches
Thready Qty Per Inch (tpi):
18 and 18

## NSN 5935-00-404-8979 Electrical Receptacle Connector - Page 2 of 2



1	.750 inches and 2.000 inches
	erminal Location:
	Back single mating end single contact grouping
	Contact Material:
c	Copper alloy single mating end single contact grouping
	Contact Surface Treatment:
Ģ	Gold single mating end single contact grouping and silver single mating end single contact groupin
h	nsert Material:
F	Rubber single mating end
Т	erminal Type:
S	Solder well single mating end single contact grouping
S	Shell Material:
Α	luminum alloy
S	Shell Surface Treatment:
C	Cadmium
h	ncluded Contact Quantity:
8	single mating end single contact grouping
h	ncluded Contact Type:
F	Round pin single mating end single contact grouping
F	Precious Material And Location:
C	Contact surfaces gold and contact surface silver
F	Precious Material And Weight:
0	.008 gold grains, troy and 0.008 silver grains, troy
F	Precious Material:
Ċ	Gold and silver
T	hread Series Designator:
	Ins and uns
	Shelf Life:
	I/a
ι	Init Of Measure:
	-
	Demilitarization:
	iig:
Α	.039b0