Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-405-1196

Body Style:
Straight shape
Overall Length:
2.685 inches
Overall Width:
0.610 inches
Unthreaded Mounting Hole Diameter:
0.099 inches
Distance Between Mounting Facility Centers:
2.352 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
Cadmium and chromate
Cadmium and chromate
Included Contact Quantity:
Included Contact Quantity:
Bifurcated spring single mating end single contact grouping
-
FIEUDUS MALEITAI ATTU METYTIL.

0.036 gold grains, troy and 0.036 silver grains, troy



Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0