

View Online at https://aerobasegroup.com/nsn/5935-00-405-1260

N/a

| view Online at https://aeiobasegroup.com/hsi/3933-00-403-1200                        |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Straight shape w/jackscrew   |
| Overall Length:  |
| Between 2.115 inches and 2.135 inches  |
| Overall Height:  |
| 4.100 inches   |
| Overall Width:   |
| Between 0.802 inches and 0.840 inches  |
| Environmental Protection:  |
| Thermal shock resistant  |
| Unthreaded Mounting Hole Diameter:   |
| 0.149 inches   |
| Distance Between Mounting Facility Centers:  |
| Between 1.740 inches and 1.760 inches  |
| Threaded Device Type:  |
| Coupling facility  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 36 single mating end   |
| Polarization Method:   |
| Polarization boss  |
| Connector Locking Method:  |
| Jackscrew  |
| Operating Tempurature Rating:  |
| Between -54.0 degrees celsius and 125.0 degrees celsius                              |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.138 inches   |
| Insert Material:   |
| Plastic diallyl phthalate glass filled single mating end                             |
| Insert Material Specification:   |
| Mil-m-14, ty sdg-f military specification single material response single mating end |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/c  |

Electrical Receptacle Connector Body - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.