NSN 5935-00-405-1283

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-405-1283

Body Style:

Straight shape

Overall Length:

1.300 inches

Overall Height:

Between 1.181 inches and 1.196 inches

Overall Width:

Between 2.861 inches and 2.871 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.281 inches and 0.285 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.558 inches and 0.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.441 inches and 2.449 inches

Distance From Mounting Shoulder To Front Face:

Between 0.541 inches and 0.551 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-41 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 3rd contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

NSN 5935-00-405-1283

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Gold
Included Contact Quantity:
4 single mating end 2nd contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0