## NSN 5935-00-405-1550

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-405-1550

**Body Style:** Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Height:** 0.688 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 325.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Cadmium and chromium

**Insert Material Specification:** 

Qq-s-698 federal specification single material response

**Shell Material Specification:** 

Mil-p-19833, ty gdi-30f military specification single material response single mating end

## NSN 5935-00-405-1550

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 15 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.