NSN 5935-00-405-1554

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-405-1554

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
6.250 inches
Overall Diameter:
2.719 inches
Environmental Protection:
Moisture resistant
Cable Entrance Diameter:
Between 1.188 inches and 1.625 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40-56 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 216.0 and 144.0 and 72.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded shell
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
16
Thread Size:
2.500 inches

NSN 5935-00-405-1554

Electrical Plug Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping or gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end and rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416, type 2, cl c federal specification single treatment response **Included Contact Quantity:** 85 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material:** Gold and silver **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0

--