Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-406-9528

### Body Style:

Straight edge type w/mounting flange

**Overall Length:** 

4.350 inches

### **Overall Height:**

0.849 inches

### **Overall Width:**

0.330 inches

#### **Environmental Protection:**

Fire resistant

### **Unthreaded Mounting Hole Diameter:**

#### 0.125 inches

**Distance Between Mounting Facility Centers:** 

4.031 inches

#### **Board Accommodated Length:**

3.578 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Connector Locking Method:**

Friction

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Solder stud single mating end single contact grouping

### Insert Material Specification:

Mil-m-14 ty gdi-30f military specification all material responses single mating end

## Included Contact Quantity:

44 single mating end single contact grouping



Included Contact Type:

Leaf spring single mating end single contact grouping

### **Special Features:**

Body has slots to accept optional polarization key

## Precious Material And Location:

Contact surfaces gold

# **Precious Material And Weight:**

0.044 gold grains, troy

### **Precious Material:**

Gold

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.