Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-407-1616

Thread Direction: Page the set of the set o			
Right-hand Right-hand Overall Widht: 1.156 inches Overall Widht: 0.900 inches Cable Opening Diameter: 0.562 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Size Designation: 14 Mouning Facility Type And Quantity: 14 Hreaded Coupling Thready Gity Per Inch (tpl): 20 Rottack Rottack Surface Treatment: Cachnium Stright type wicable clamp Surface Treatment: Cachnium Stright type wicable clamp Surface Treatment: Cachnium Stright type wicable clamp Surface Treatment: Cachnium Thread Stripe Designator: Cachnium Thread Stripe Designator: Cachnium Thread Stripe Designator: Cachnium Thread Stripe Designator: Cachnium Thread Stripe Desig			
Right-hand Overall Height: 1.156 inches Overall Width: 0.906 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 1 Size Designation: 14 Mounting Facility Type And Quantity: 1 1 threaded coupling Thread Quy Per Inch (tpi): 20 Thread Size: 0.512 inches Muninum alloy Surface Treatment: Cadnium Style Designator: Strade Treatment: Cadmium Style Designator: Strade Treatment: Cadmium Thread Size Cadmium Style Designator: Cadmium Thread Size Insteile Cadming Strafee Treatment: Cadmium Thread Size Insteile Cadming Strafee Treatment: Cadmium Thread Size Insteile Cadming Strafee Treatment: Cadmium Thread Si			
Overall Height: 1.156 inches Overall Width: 0.906 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Size Designation: 14 Mounting Facility Type And Quantity: 15 16 Mounting Facility Type And Quantity: 17 17 Mounting Facility Type And Quantity: 18 18 19 20 Stried Coupling Murium alloy Surface Treatment: Cadmium Stright type wicable clamp Surface Treatment: Cadmium Thread Stries Designator: Inter Treated Stries Designator: Inter Treated Stries Designator:			
1.156 inches Overall Width: 0.906 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Size Designation: 14 Mounting Facility Type And Quantity: 1 14 Mounting Facility Type And Quantity: 1 1 1 Mean Coupling Thready Qty Per Inch (tpi): 20 21 Nerad Size: 0.812 inches Material: 0.812 inches Material: 0.812 inches Surface Treatment: Cadmium Straight type wicable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Naterial: Naterial: Cadmium Thread Series Designator: Unef Surface Treatment: Cadmium Thread Series Designator: Unef SurfaceTreatment: Cadmium Thread Series Designator: Unef Na Unit Measure: Na Demilitarization: Na Demilitarization: Na Fig:	-		
Overall Width: 0.906 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Stoe Designation: 14 Mounting Facility Type And Quantity: 1 Thready Coupling Thready Que Per Inch (tpi): 20 Alterial: Auminum alloy Strate Teatment: Cadmium Strate Teatment: Cadmium Strate Teatment: Cadmium Thread Series Designator: Interdation Cadmium Strates Teatment: Cadmium Thread Series Designator: Interdation Cadmium Thread Series Designator: Interdation Thread Series Designator: Interdation: Naterial: Interdation: Interdation: Interdation: Interdation: Interdation: Interdation: Interdating Interdating Interdation Interdating In			
0.906 inches Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Cable Opening Quantity: 1 Size Designation: 1 Variated Coupling Cable Opening Quantity: 1 Variated Coupling Thready Cap Per Inch (tpi): 20 Thready Cap Per Inch (tpi): 20 Thread Size: 20 Autinium alloy Surface Treatment: Cadmium Style Designator: Strige Treatment: Cadmium Catreatment: Cadmi			
Cable Opening Diameter: 0.562 inches Cable Opening Quantity: 1 Size Designation: 14 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 20 Privated Size: 0.812 inches Material: Aluminum alley Surface Treatment: Cadmium Style Designator: Straface Treatment: Cadmium Straface Treatment: Cadmium Straface Treatment: Cadmium Straface Treatment: Cadmium Thread Series Designator: Straface Treatment: Cadmium Thread Series Designator: Via Shell Lite: Na Mainting Series Designator: Straface Treatment: Cadmium Thread Series Designator: Na Shell Lite: Na Thread Series Designation: Stres Designatin Cadmine <tr< th=""><th></th><th></th><th></th></tr<>			
0.682 inches Cable Opening Quantity: 1 Size Designation: 1 4 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strajet Type wotable damp Surface Treatment: Cadmium Thread Series Designator: Unef Shel Lite: Na Shel Distable Series Designator: Style Designator: Style Designator: Style Designator: Cadmium Thread Series Designator: Style Design			
Cable Opening Quantity: 1 1 Size Designation: 14 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thready Qty Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Style Designator: Cadmium Thread Series Designator: Unef Sheff Life: Na Unit Of Measure: - Denilitarization: No Fig:			
1 Size Designation: 14 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Cadmium Thread Series Designator: Unef Shelf Life: Na Unef Shelf Life: Na Did Measure: Theod Series Designator: Na Did Measure: Thread Series Designator: Na Shelf Life: Na Fig: Theid Series Designator:			
Size Designation: 14 14 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 20 Thread Size: 20 Shafe Size: 20 Shafe Size: 20 Shafe Treatment: 20 Strigter Tre			
14 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Dinf Genesure: Int of Measure: Intertiation: Na Straight type in the stra			
Nounting Facility Type And Quantity: 1 threaded coupling Thready Cay Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Stratight type w/cable clamp Cadmium Thread Series Designator: Unef Shelf Life: Na Dint Of Measure: The Component Com			
1 thread coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Cadmium Thread Series Designator: Unef Shelf Life: N/a Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Thready Quy Per Inch (tpi): 20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straface Treatment: Cadmium Style Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Unef Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:			
20 Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Style Designator: Straight type w/cable clamp Straight type w/cable clamp Style Designator: Straight type w/cable clamp Straight type w/cable clamp Style Designator: Straight type w/cable clamp Style Designator: Straight type w/cable clamp Style Designator: Straight type w/cable clamp Style Designator: Style Designa			
Thread Size: 0.812 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Dint Of Measure: Demilitarization: No Fig:			
0.812 inches Material: Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:			
Material:Aluminum alloySurface Treatment:CadmiumCadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Aluminum alloy Surface Treatment: Cadmium Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unef Deli Def Measure: Pemilitarization: No			
Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:			
Style Designator:Straight type w/cable clampSurface Treatment:CadmiumCadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
N/a Unit Of Measure: Demilitarization: No Fiig:			
Unit Of Measure: Demilitarization: No Fiig:			
 Demilitarization: No Fiig:			
Demilitarization: No Fiig:	Unit Of Measure:		
No Fiig:			
Fiig:			
A10100			
	A10100		