

View Online at <https://aerobasegroup.com/nsn/5935-00-408-9851>

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 3.185 inches and 3.215 inches

Overall Height:

Between 0.530 inches and 0.550 inches

Overall Width:

Between 0.430 inches and 0.450 inches

Environmental Protection:

Vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 2.940 inches and 2.960 inches

Board Accommodated Width:

Between 0.080 inches and 0.104 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Fixed inter-contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.