
NSN 5935-00-409-5286

Tip Jack - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 1.094 inches Mounting Bushing Length: 0.500 inches **Body Length:** 0.750 inches **Overall Diameter:** 0.500 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 750.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.086 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches **Capacitance In Picofarads:** 4.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic insulator

NSN 5935-00-409-5286

Tip Jack - Page 2 of 2

Material:

Plastic insulator

Surface Treatment:

Nickel spring

Surface Treatment:

Nickel spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400

