## NSN 5935-00-410-2276

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-410-2276 **Thread Class:** 2b **Thread Pitch Diameters:** +0.1000/+0.1049 inches **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 1.509 inches and 1.513 inches **Overall Diameter:** 2.344 inches **Environmental Protection:** Explosion proof and fungus resistant and moisture resistant and thermal shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 20.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): **Thread Size:** 2.000 inches **Terminal Location:** Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end 2nd contact grouping

**Insert Material:** 

Plastic tetrafluoroethylene single mating end

## **NSN 5935-00-410-2276**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
3 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end 2nd contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.021 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0