NSN 5935-00-410-2294

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-410-2294 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 2.073 inches and 2.083 inches **Overall Height:** 0.630 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 21 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping

Shell Material: Steel

NSN 5935-00-410-2294

Fiig: A039b0

Mil-std (military Standard):

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No