NSN 5935-00-410-2713

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-410-2713

Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
0.774 inches
Overall Diameter:
0.250 inches
Environmental Protection:
Moisture resistant and salt water resistant
Distance From Mounting Shoulder To Front Face:
0.240 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic polychlorotrifluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550,
class 4 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping
Shell Material:

Copper alloy

NSN 5935-00-410-2713

Electrical Receptacle Connector - Page 2 of 2



Shell Surface	Treatment:
---------------	------------

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204, type 1, class 2, grade c military specification 1st treatment response and mil-c-14550, class 4 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces and shell surface gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.